

3.3V / 622 Mbps InGaAs PIN-TIA Receiver

PT-5530 Series

InGaAs PIN-TIA WITH RECEPTACLE

FEATURES

- 2 InGaAs/InP PIN Photodiode with AGC transimpedance amplifier
- 2 Differential ended output
- 2 Single +3.3V operation
- 2 Speed up to 622 Mbps
- 2 - 40 ~ +85 °C operation temperature

DESCRIPTION

PT-5530 series are designed as optical signal receivers with AGC transimpedance amplifier. Their wide dynamic ranges, differential outputs are suited for telecommunications, especially SONET OC-12 / SDH STM-4, and Fiber Channel.

AC / ELECTRICAL AND OPTICAL CHARACTERISTICS (T _c =25°C)						
Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
	Detection Range		1100	1310	1650	nm
G	Differential Gain	AC coupled, load=50 Ω	16	20	24	V/mW
BW	Bandwidth	-3 dB point	450			MHz
Psat	Saturation Power	λ =1300nm	-3		-	dBm
Sens	Sensitivity	BER=10 ⁻¹⁰ @622Mbps	-	-31	-30	dBm
Rout	Output Resistance		-	50	65	ohm
	Operation Speed			622		Mbps

DC / ELECTRICAL CHARACTERISTICS (T _c =25°C)					
Symbol	Parameter	Min.	Typ.	Max.	Unit
V _{CC}	Power Supply	3.15	3.3	3.45	V
I _{CC}	Supply Current (no load)	-	-	40	mA

ABSOLUTE MAXIMUM RATING (T _c =25 °C)			
Symbol	Parameter	Value	Unit
V	Voltage	4.5	V
T _{opr}	Operating Temperature	-40~+85	°C
T _{stg}	Storage Temperature	-40~+85	°C

MECHANICAL DIMENSION (mm) and PIN ASSIGNMENT

OPTOWAY TECHNOLOGY INC.

No.38, Kuang Fu S. Road, Hu Kou, Hsin Chu Industrial Park, Hsin Chu, Taiwan 303

Tel: 886-3-5979798


Fax:886-3-5979737

e-mail: sales@optoway.com.tw

[http:// www.optoway.com.tw](http://www.optoway.com.tw)

10/1/2002 V1.0

Note: Specifications subject to change without notice.



ORDER INFORMATION

Part No.: P T - 5 5 3 0 -

Code	PIN Assignment
Blank	Type A
B	Type B

Code	Connector Type
F	FC/PC
FB	FC/PC (Board Mount)
T	ST/PC
S	SC/PC
SB	SC/PC (Board Mount)
